

**Bewehrungsmatten sind ab Lager sofort verfügbar.**

Art.-Nr.	Typ	Format m	Teilung längs/quer mm	Ø längs/quer mm	Q-längs mm <sup>2</sup> /m	Q-quer mm <sup>2</sup> /m	Gewicht kg/Tfl
<b>Bewehrungsmatten Typ K - kaltverformter, profilierter Stahldraht, Betonstahl B500A</b>							
312 568	K 188	5.00 x 2.00	150/150	6.0/6.0	188	188	30.2
312 569	K 196	5.00 x 2.00	100/100	5.0/5.0	196	196	30.8
312 570	K 283	5.00 x 2.00	100/100	6.0/6.0	283	283	44.4
312 571	K 335	5.00 x 2.00	150/150	8.0/8.0	335	335	53.7
<b>Bewehrungsmatten Static - kaltverformter, profilierter Stahldraht, Betonstahl B500A</b>							
312 759	Z 248.6	6.00 x 2.00	150/150	6.0/7.0	248	257	41.7
312 760	Z 348.5	5.00 x 2.00	150/150	7.0/8.0	348	335	46.3
312 761	Z 348.6	5.00 x 2.00	150/150	7.0/8.0	348	335	56.4
312 762	Z 442.5	5.00 x 2.00	150/150	8.0/9.0	442	424	58.6
312 763	Z 442.6	6.00 x 2.00	150/150	8.0/9.0	442	424	71.3
312 764	Z 558.5	5.00 x 2.00	150/150	8.5/10.0	558	524	73.2
312 765	Z 558.6	6.00 x 2.00	150/150	8.5/10.0	558	524	89.1
<b>Bewehrungs- / Schlaufenmatten artec 500 - Betonstahl B500B</b>							
314 980	B 335.39	3.90 x 2.25	150/150	6.0/8.0	335	335	46.9
314 981	B 335.48	4.80 x 2.25	150/150	6.0/8.0	335	335	57.7
314 982	B 335.54	5.40 x 2.25	150/150	6.0/8.0	335	335	64.9
314 983	B 335.63	6.30 x 2.25	150/150	6.0/8.0	335	335	75.7
314 984	B 424.48	4.80 x 2.25	150/150	6.0/9.0	424	424	71.9
314 985	B 424.54	5.40 x 2.25	150/150	6.0/9.0	424	424	80.9
314 986	B 424.63	6.30 x 2.25	150/150	6.0/9.0	424	424	94.4
315 206	B 524.48	4.80 x 2.25	150/150	7.0/10.0	524	524	89.3
315 026	B 524.54	5.40 x 2.25	150/150	7.0/10.0	524	524	100.5
314 987	B 524.63	6.30 x 2.25	150/150	7.0/10.0	524	524	117.2
315 458	B 754.63	6.30 x 2.25	150/150	8.0/12.0	754	754	168.9
314 992	W 335.25	2.50 x 2.25	150/150	6.0/8.0	335	424	32.3
316 003	W 335.27	2.70 x 2.25	150/150	6.0/9.0	335	424	34.5
314 994	W 335.32	3.20 x 2.25	150/150	6.0/8.0	335	424	37.4
316 221	W 424.32	3.20 x 2.25	150/150	6.0/10.0	424	524	46.5
<b>Bewehrungsmatten topar-M/Wama 500 - Betonstahl B500B</b>							
314 999	HX 335.51	5.10 x 2.10	150/150	8.0/8.0	335	335	56.4
315 000	HX 335.63	6.30 x 2.10	150/150	8.0/8.0	335	335	69.7
315 001	HX 424.51	5.10 x 2.10	150/150	9.0/9.0	424	424	71.3
315 002	HX 424.63	6.30 x 2.10	150/150	9.0/9.0	424	424	88
315 003	HX 523.51	5.10 x 2.10	150/150	10.0/10.0	523	523	88.1
315 004	HX 523.63	6.30 x 2.10	150/150	10.0/10.0	523	523	108.8